

1. Product and Company Identification

www.rxmarine.com

Product Name RXSOL-16-1003-025
Product Type CARBON REMOVER-II

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333 / 5555 / 9999 / 27611360
Fax +91 22 2781 1318 ::AOH :0091 9821214367
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemica Name	Concentration	CAS Number	EC Number	R Phrases*	
1,2-Dichlorobenzene	30-60	95-50-1	202-425-9	22, 36/37/38, 50/53	S
Emulsified Xylenol	10-30	1300-71-6	215-089-3	24/25, 34, 51/53	X
Emulsifiable Liq of Aliphatic & Aromatic, unspecified	10-30	64742-94-5	265-198-5	65, 66, 51, 53	T
Naphtha(petroleum)hydrosulfurizedheavy	10-30	64742-82-1	265-185-4	65, 66	X

*See Section 16

3. Hazards Identification

www.rxmarine.com



Toxic



Corrosive

Odour	Unpleasant odour, Strong smell of phenol.
Appearance	Liquid, brown, dispersible in water.
Contact with eyes	Can cause damage to the eyes.
Contact with skin	Causes burns (R34), Toxic in contact with skin and if swallowed (R24/25).
Inhalation	May cause severe irritation, May cause dizziness, confusion, headache or stupor, In cases of severe exposure, anaesthesia (R42/43).
Ingestion	Toxic if swallowed (R25).
	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R50/53).

4. First Aid Measures

www.rxmarine.com

Dangerous for the Environment	Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water. If doubt or symptoms persist, seek medical attention. Contaminated clothing should be laundered before reuse.
Contact with eyes	If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes. Irrigate eyes thoroughly under running water. Remove contact lenses if present and continue flushing. Seek immediate medical attention. Continue flushing with water until medical help arrives.
Ingestion	Never make an unconscious person vomit or drink fluids. Give plenty of water to drink. Do not induce vomiting. Seek immediate medical attention.
Inhalation	Remove patient to fresh air. Keep warm and at rest, in a half upright position. Loosen clothing. When in doubt or symptoms persist, seek medical attention.
General	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

5. Fire-fighting Measures

www.rxmarine.com

- Flash point >70 deg C (CC)
- Decomposition products may include phosgene, Decomposition products may include carbon oxides
- In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide (S43)
- Substance evolves toxic fumes, wear self-contained breathing apparatus
- Prevent run off water from entering drains if possible
- Use water spray or fog to knock down and absorb corrosive fumes
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback

6. Accidental Release Measures

www.rxmarine.com

Personal Precautions	Wear protective clothing as per section 8. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.
Environmental Precautions	Do not allow to enter public sewers and water courses.
Immediate Actions	Use appropriate containment to avoid environmental contamination (S57).
Clean Up Actions	Absorb spillage in inert material and shovel up. Ventilate the area and wash spill site after material pick-up is complete.
Special Precautions	Wear protective clothing as per section 8 Avoid release to the environment. Refer to special instructions/Safety data sheet. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.

7. Handling and Storage

www.rxmarine.com

Handling	See Section 8 Eye wash bottles should be available Avoid contact with skin and eyes (S24/25)
Storage	Keep only in the original container in a cool, well ventilated place (S3/9/49)

8. Exposure controls and personal protection

www.rxmarine.com

Exposure Limits	TLV (TWA) 20 ppm, 122 mg/m ³ (1,2-Dichlorobenzene)
Exposure controls	The undiluted product must not be used in a confined space without good ventilation
Occupational exposure controls	Wear approved respirator if exposure likely to exceed MEL/OES Wear goggles giving complete eye protection and protective clothing, including eye/face protection and gloves (neoprene or nitrile are recommended)



Respirator



Gloves



Goggles



No_Smoking

9. Physical and chemical properties

www.rxmarine.com

Odour	Unpleasant odour, Strong smell of phenol
Appearance	Liquid, pale to brown, dispersible in water
pH	N/A
Boiling point	> 100 °C at 760 mm /Hg
Vapour pressure	not known
Vapour density	(air = 1) >01
Freezing point	