

1. Product and Company Identification

www.rxmarine.com

Product Name **RXSOL-20-2044-210**
Product Type **Wax Cleaner Paraffin (Slack)**

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Ready Stock: Mumbai, Kandla, Kolkata, Vishakhapatnam, Chennai, Fujairah, Muscat, Canada

Phone +91 22 65113333 / 5555 / 9999 / 27611360
Fax +91 22 2781 1318 :::AOH :0091 9821214367
Email 123@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

| Substance name | Contents | CAS No | EC No | Index No | Classification |
|------------------------------------|---------------|------------|-----------|--------------|--|
| Alkylated sulfonic acid derivates | 25 to 50 % | 68584-22-5 | 271-528-9 | | C; R34 |
| Proprietary Blend | 8 to 10 % | ----- | ----- | ----- | ----- |
| 1,2,4-trimethylbenzene | 5 - 10 % | 95-63-6 | 202-436-9 | 601-043-00-3 | R10 Xn; R20 Xi; R36/37/38 N; R51-53 |
| Naphthalene | < 3 % 91-20-3 | 91-20-3 | 202-049-5 | 601-052-00-2 | Carc. Cat. 3; Xn; R22 N; R50-53 |
| Solvent naphtha (petroleum), heavy | 40 to 50 % | 64742-94-5 | 265-198-5 | 649-424-00-3 | Xn; R65 aromatic |
| Fatty Amine | 2 - 5% | ----- | ----- | ----- | ----- |

3. Hazards Identification

www.rxmarine.com

| | |
|---------------------------|---|
| Risk Phrases | Causes burns. Harmful if swallowed. |
| Primary route of exposure | Vapours inhalation. Skin and eyes contact. Symptoms relating to use |
| Inhalation | Corrosive to respiratory system |
| Skin contact | Irritative Causes burns |
| Eye contact | Risk of serious damage to eyes. |
| Ingestion | Abdominal pain, nausea. Burning sensation. |

4. First Aid Measures

www.rxmarine.com

| | |
|--------------|---|
| Inhalation | Assure fresh air breathing. Obtain medical attention if breathing difficulty persists. Assure fresh air breathing. Obtain medical attention if breathing difficulty persists. |
| Skin contact | Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinsing. Obtain medical attention if irritation develops. |
| Eye contact | Rinse immediately with plenty of water. Contact ophthalmologist immediately. |
| Ingestion | Rinse mouth. Do not induce vomiting because of corrosive effects. Call a physician immediately. |

5. Fire-fighting Measures

www.rxmarine.com

| | |
|-------------------------|---|
| Extinguishing media | All extinguishing media can be used. |
| Specific hazards | High temperature may liberate dangerous gases |
| Protection against fire | Do not enter fire area without proper protective equipment, including respiratory protection. |
| Special procedures | Exercise caution when fighting any chemical |

6. Accidental Release Measures

www.rxmarine.com

| | |
|---------------------------|--|
| Personal precautions | Equip cleanup crew with proper protection. Respiratory protection equipment may be necessary. |
| Environmental precautions | Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. |
| Clean up methods | Clean up any spills as soon as possible, using an absorbent material to collect it. Dilute residues and flush. |

7. Handling and Storage

www.rxmarine.com

| | |
|-------------------------------------|---|
| Precautions in handling and storage | Good ventilation of the workplace required. |
| Storage | Store in dry, well-ventilated area. Do not store in corrodable metal. Storage - away from : Strong bases. |
| Handling | Ensure prompt removal from eyes, skin and clothing. Wash hands and other exposed areas with mild soap and water before smoke and when leaving work. |

8. Exposure controls and personal protection

www.rxmarine.com

| | |
|------------------------------|---|
| Respiratory protection | Approved dust or mist respirator should be used if airborne particles are generated when handling this material. |
| Hand protection | Gloves. |
| Skin protection | If skin contact or contamination of clothing is likely, protective clothing should be worn. |
| Eye protection | Safety glasses. |
| Ingestion | When using, do not eat, drink or smoke |
| Industrial hygiene | Provide local exhaust or general room ventilation to minimize dust and/or vapour concentrations. |
| Occupational Exposure Limits | Solvent naphtha (petroleum), heavy aromatic : TLV® -TWA [mg/m ³] : 100 - 525 1,2,4-trimethylbenzene : TLV® -TWA [mg/m ³] : 125 1,2,4-trimethylbenzene : TLV® -TWA [ppm] : 25 1,2,4-trimethylbenzene : TGG 15 min (nl) (mg/m ³) : 200 1,2,4-trimethylbenzene : TGG 8 uur (nl) (mg/m ³) : 100 Naphthalene : TLV® -TWA [mg/m ³] : 52 Naphthalene : TLV® -TWA [ppm] : 10 Naphthalene : TLV® -TWA [ppm] : 10 Naphthalene : TGG 15 min (nl) (mg/m ³) : 80 Naphthalene : TGG 8 uur (nl) (mg/m ³) : 50 |

9. Physical and chemical properties

www.rxmarine.com

Product properties

| | |
|-------------------------|--------------------|
| Physical state at 20 °C | Liquid. |
| Colour | Clear Pale / Brown |
| Odour | Pungent |
| Pour point [°C] | |