

1. Product and Company Identifaction

www.rxmarine.com

Product Name **Chloro Clean Rx**
Part Number **RXSOL-20-2096-025**

Company Details:
RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333 / 5555 / 9999
Fax +91 22 2781 1318 :::AOH :0091 9821214367
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Ingredint Name	Conc. %	CAS Number
Hydrotreated Hydrocarbons	5% - 60%	---
Synthetic Polyamide/Furanones	10 - 30%	---
Synthetic Pyridine	10-25 %	---
Unclassified Mixture	5 -20 %	---

3. Hazards Identification

www.rxmarine.com

Human Health Hazards	Harmful if swallowed
Safety Hazards	Irritant. Prolonged contact may lead to dermatitis.
Environmental Hazards	Raw Ingredients are biodegradable and readily dissolve in water.

4. First Aid Measures

www.rxmarine.com

Symptoms and effects: Ingestion may cause nausea, vomiting, convulsions and unconsciousness

Inhalation: Remove to fresh air. If rapid recovery does not occur, obtain medical attention.

Skin: Wash with soap and water. Get medical attention if irritation develops or persists

Eye: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Do not delay. Do not induce vomiting. Give water to drink, providing patient is conscious. Obtain medical attention immediately.

Advice to Physicians: Treat symptomatically following cases of gross over exposure, investigation of liver, kidney and eye function may be advisable. Records of such incident should maintain for further references.

5. Fire-fighting Measures

www.rxmarine.com

Specific Hazardous	Flammable above 95°C
Fire Extinguishing Media	Alcohol resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only
Specific Methods	Do not use water in a jet
Protective Equipment	Full protective clothing and self contained breathing apparatus
Other Information	Keep adjustment containers cool by spraying with water

6. Accidental Release Measures

www.rxmarine.com

Personal Precautions: Avoid contact with skin, eyes, clothing. Ventilate contaminated area thoroughly. Do not breathe mists, aerosols. No smoking. Extinguish naked flames. Remove ignition sources. Avoid sparks.

Personal Protection: Wear monogoggles, PVC gloves, gauntlet type disposable one-piece coated overall without integral hood, safety boots-rubber, knee-length. For guidance on respiratory protection see section 8.

Environmental Precautions: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform the local authorities if this cannot be prevented.

Clean up Methods -

Small Spillage: Absorb or contain liquid with sand, earth or spill control material. Shovel up and place in a labeled, sealable container for subsequent safe disposal. Flush contaminated area with plenty of water.

Large Spillage: Transfer to a labeled, sealable container for product recovery or safe disposal. Otherwise treat as for small spillage.

Technical measures:

Working place and methods should be worked out in order to avoid direct contact. Work and storage area should be well ventilated. A closed rinse water system with filtration and reuse of clear water is recommended.

Handling: Do not breathe fumes or vapours from heated product. Avoid prolonged or repeated contact with skin, eyes and clothing.

Handling Temperature Storage: Ambient 60°C Max

Storage Temperature Tank Cleaning: Keep container tightly closed. Tanks must be clean, dry and rust free.

Recommended Materials: Most metals of HMHDPE & steel. Construction are suitable.

Engineering Control Measures: Use only in well ventilated areas. Use local exhaust ventilation.

Hygiene Measures: Launder overall and under garments regulatory. Dispose of soiled gloves.

Respiratory Protection: If engineering controls do not maintain air borne concentrations to level which is adequate to protect worker health, select respiratory protect equipment suitable for the specific conditions of use and meeting relevant legislation. use appropriate positive pressure breathing apparatus. Where air filtering respirators are suitable select an appropriate combination of mask and filter. Select a filter suitable for combined particulate / organic gases and vapors (boiling point >65°C)

Physical state

Liquid with a pungent smell.

Odour

Paraffin-like

Colour

Straw

Boiling Point