1. Product and Company Identifaction

www.rxmarine.com

Product Name : RXSOL-30-1091-025

Product Type : Valve Cleaner MAchinery Parts Cleaning Solvent Mixture

Company Details:

RX MARINE INTERNATIONAL 105, A wing , BSEL , TECH PARK. VASHI ,NEW BOMBAY 400703 INDIA

Phone : +91 22 65113333 / 5555 / 9999 / 27611360 Fax : +91 22 2781 1318 :::AOH :0091 9821214367

Email : mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name Naphtha(petroleum), hydrotreated heavy Concentration

CAS Number

EC Number

R Phrases*

65,66

Syml Xn

tha(petroleum), 60-100 64742-48-9 265-150-3

*See Section 16

Inhalation

General

3. Hazards Identification

www.rxmarine.com

Odour Smells of hydrocarbon

Appearance Liquid, colourless, insoluble in water

Contactwith eyes Causes irritation

Contact with skin Prolonged skin contact will result in defatting of the skin, leading to irritation, and in

some cases, dermatitis

chronic pneumonitis may develop

Ingestion The ingestion of significant quantities may cause nausea/vomiting, Harmful: may cause lung damage if swallowed (Re

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45)

Vapours may cause drowsiness and dizziness (R67), In cases of severe exposure, anaesthesia may develop, In cases of

4. First Aid Measures

www.rxmarine.com

Contact with skin Remove contaminated clothing. Wash affected area with plenty of soap and water

Contaminated clothing should be laundered before reuse Seek medical attention if irritation persists.

Contact with eyes If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes Irrigate eyes thorough

eyelids Seek medical attention if irritation persists

Ingestion Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate m

vomiting occurs turn patient on side

Give water or milk to drink Obtain immediate medical attention.

Inhalation Remove patient to fresh air Keep warm and at rest, in a half upright position. Loosen clothing Seek medical attention

General In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45)

5. Fire-fighting Measures

www.rxmarine.com

- Auto-ignition point >200 deg C at 760 mm Hg.
- Lower flammability limit 0.6%(in air), Upper flammability limit 7%(in air), Flash point 63 deg C (CC).
- Decomposition products may include carbon oxides.
- In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide (S43).
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.
- Keep container(s) exposed to fire cool, by spraying with water.

6. Accidental Release Measures

www.rxmarine.com

Personal Precautions Wear protective clothing as per section 8

Environmental Precautions Do not allow to enter public sewers and watercourses

Immediate Actions Use appropriate containment to avoid environmental contamination (S57)

Clean Up Actions Absorb spillage in inert material and shovel up Ventilate the area and wash spill site after material pick-up is complete

Special Precautions Wear protective clothing as per section 8 Vapours are heavier than air and may travel considerable distances to a sou

flashback Wear suitable respiratory protection

7. Handling and Storage

www.rxmarine.com

Handling Wear protective clothing as per section 8 During fumigation/spraying wear suitable respiratory equipment (S42).Av

skin and eyes (S24/25) Eyewash bottles should be available . Keep away from sources of ignition - No Smoking (S16)

Storage Keep container tightly closed, in a cool, well ventilated place (S3/7/9) Keep away from open flames, hot surface

ignition.

8. Exposure controls and personal protection

www.rxmarine.com

Exposure Limits TLV (TWA) 275 mg/m3 (White spirit (de-aromatized)).

Exposure controls No special ventilation is required unless the product is used in a spray formThe undiluted product must not be used in

without good ventilation.

Occupational exposure controls Wear suitable protective clothing, including eye/face protection and gloves (neoprene or nitrile are recomm

protection may be required under exceptional circumstances when excessive air contamination exists Wear appr

exposure likely to exceed MEL/OES.

9. Physical and chemical properties

www.rxmarine.com

Odour Smells of hydrocarbon

Appearance Liquid, colourless, insoluble in water

pH not applicable

Boiling point $$190\ ^{\circ}\text{C}$$ to $203\ ^{\circ}\text{C}$ at $760\ \text{mm}$ /Hg

Vapour pressure 40 Pa at 20 deg C Vapour density (air = 1) 5.4 Freezing point unknown

Insoluble in water

Specific gravity (water=1) 0.79

Lower flammability limit 0.6%(in air)

Upper flammability limit 7%(in air)

Flash point 63 deg C (CC)

Auto-ignition point > 200 deg C at 760 mm Hg

Log Pow 3.5 - 4.7

Viscosity 1.59 cST @ 25 deg C

10. Stability and reactivity

www.rxmarine.com

- This article is considered stable under normal conditions.
- Avoid overheating, Keep away from naked flames, incandescent or hot surfaces.

11. Toxicological information

www.rxmarine.com

Toxicological information LD50 (oral,rat) >2000 mg/kg.LD50 (dermal) :>2000 mg/kg.LC50 (inhalation) :>5 mg/l/4h

Inhalation Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

Contact with skin Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis

Contact with eyes In cases of severe exposure, irritation may develop

Ingestion May cause gastro-intestinal disturbances .Aspiration hazard . Harmful: may cause lung damage if swallowed (R65)

Carcinogenicity No evidence of carcinogenic effects

12. Ecological information

www.rxmarine.com

Ecotoxicity Low toxicity to fish.LC50 (rainbow trout) >1000 mg/l (96 hr).IC50 (algae) >100 mg/l (72 hr)

Mobility Insoluble in water

Persistence and Biodegradability Biodegradability 67 % (OECD 301F)
Bioaccumulation Potential Low bioaccumulation potential

Adverse Effects No environmental problems are expected when the product is used / handled correctly.

In its intended use, the product will not be released into the environment.

13. Disposal considerations

www.rxmarine.com

Classification EU Waste class: 07.01.

Disposal considerations Do not discharge into drains or the environment, dispose to an authorised waste collection point Disposal should be

local, state or national legislation

14. Transport information

www.rxmarine.com

- Not classified as hazardous for transport

15. Regulatory information

www.rxmarine.com

Risk Phrases Safety Phrases Harmful: may cause lung damage if swallowed (R65) Repeated exposure may cause skin dryness or cracking (R66) Do not breathe vapour/fumes(S23) Avoid contact with skin (S24) Wear suitable gloves and eye/face protection (S37 do not induce vomiting: seek medical advice immediately and show this container or label (S62)

16. Other information

www.rxmarine.com

Text of R and S phrase codes used in this safety data sheet:- R65: Harmful: may cause lung damage ifswallowed; R66: Repeated exposure may cause skin dryness or cracking. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties. The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet Do not use for other application(s) without seeking advice from manufacturer. This Safety Data Sheet is provided in compliance with The Dangerous Preparations Directive This Safety Data Sheet is provided in compliance with The Dangerous Preparations Directive This Safety Data Sheet is provided in compliance with The Data Sheet is provided in compliance with T

DISCLAIMER OF LIABILITY: The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.