

1. Product and Company Identification

www.rxmarine.com

Product Name **RXSOL 70-7009-020**
Product Type **FUEL CARE 20 Ltr**

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Kolkata, Chennai, Fujairah, Muscat, Vizag, Nairobi

Phone +91 22 65113333 / 5555 / 9999 / 27611360
Fax +91 22 2781 1318 :::AOH :0091 9821214367
Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	Concentration	CAS Number	EC Number	R Phrases*
Kerosine-unspecified	60-100	64742-94-5	265-198-5	65,66, 51, 53
Naphtha(petroleum), hydro desulfurized heavy	10-30	64742-82-1	265-185-4	65,66

Fatty Alcohol Polyethoxylated Polymer Exemption 1-30%

Manganese Octoate 6535-19-9 10-20%
Tall oil hydroxyethyl imidazoline 61791-39-7 2631712 10 - 30 C 34

3. Hazards Identification

www.rxmarine.com



Harmful

Odour	Smells of hydrocarbon
Appearance	Liquid, pale yellow, insoluble in water
Contact with eyes	Causes redness and irritation
Contact with skin	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
Inhalation	In cases of severe exposure, dizziness, confusion, headache or stupor may develop
Ingestion	Harmful: may cause lung damage if swallowed (R65) Toxic to aquatic organisms, may cause long-term adverse effects in the environment (R51/53)

4. First Aid Measures

www.rxmarine.com

Ingestion	Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention
Inhalation	If vomiting occurs turn patient on side Obtain immediate medical attention Give water or milk to drink Remove patient to fresh air Seek medical attention if ill effects occur
General	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45)

5. Fire-fighting Measures

www.rxmarine.com

- Auto-ignition point >200 deg C at 760 mm Hg
- Flash point >62 deg C (CC)
- Carbon oxides may be formed
- In case of fire use water spray or fog, alcohol resistant foam, dry chemical or carbon dioxide (S43)
- Do not use water jets
- Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback
- Prevent run off water from entering drains if possible
- Wear Breathing Apparatus

6. Accidental Release Measures

www.rxmarine.com

Personal Precautions

Wear protective clothing as per section 8

Environmental Precautions

Do not allow to enter public sewers and watercourses

Immediate Actions

Do not flush spilt material into any public water system

Clean Up Actions

Contain spillage by any means possible

Special Precautions

Absorb spillage in inert material and shovel up Ventilate the area and wash spill site after material pick-up is complete

Do not allow to enter public sewers and watercourses

Personal Precautions

Wear protective clothing as per section 8

7. Handling and Storage

www.rxmarine.com

Handling

Avoid contact with skin and eyes (S24/25) Do not breathe vapours excessively Keep away from heat and sources of ignition

8

Storage

Keep only in the original container in a cool, well ventilated place (S3/9/49) Keep container tightly closed (S7) Keep away from flames, hot surfaces and sources of ignition.

8. Exposure controls and personal protection

www.rxmarine.com

Exposure Limits

TLV (TWA) 120 mg/m³ (Kerosine, unspecified) TLV (TWA) 275 mg/m³ (Naphtha (petroleum) hydrodesulfurized hydrocarbons)

Exposure controls

The undiluted product must not be used in a confined space without good ventilation No special ventilation is required if the product is used in a spray form.

Occupational exposure controls

No respiratory protection is required unless subject to contact with substance mist Where an air-purifying respirator is required EN141 or EN405, type A



Gloves Suit Goggles No_Smoking

9. Physical and chemical properties

www.rxmarine.com

Odour

Smells of hydrocarbon

Appearance

Liquid, pale yellow, insoluble in water

pH

not applicable

Boiling point

175 °C to 215 °C at 760 mm Hg

Vapour pressure

not known

Vapour density (air = 1)

>1

Melting point	not known
Insoluble in water	
Specific gravity (water=1)	0.86
Flash point	>62 deg C (CC)
Auto-ignition point	>200 deg C at 760 mm Hg
Lower explosive limit	0.6 % (in air)
Upper explosive limit	7 % (in air)

10. Stability and reactivity

www.rxmarine.com

- This article is considered stable under normal conditions
- Keep away from naked flames, incandescent or hot surfaces
- See Section 5

11. Toxicological information

www.rxmarine.com

Toxicological information	LD50 (oral) : >2000 mg/kg (Kerosine / naphtha).
Inhalation	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness.
Contact with skin	Causes redness and irritation Prolonged skin contact will result in defatting of the skin, leading to irritation, a dermatitis.
Contact with eyes	Causes redness and irritation Ingestion The ingestion of significant quantities may cause damage to lungs Carcinogenic of carcinogenic effects.

12. Ecological information

www.rxmarine.com

Ecotoxicity	This product contains components which are classified in the EU as dangerous for the environment. Toxic to aquatic life with long-term effects. LC50 96 hours fish 1-10 mg/l (Kerosine) LC50 96 hours Daphnia 10-100 mg/l (Naphtha)
Mobility	Insoluble in water
Persistence and Biodegradability	BOD 28 >60%
Bioaccumulation Potential	Hydrocarbon solvents have the potential to bioaccumulate.
Other Adverse Effects	No environmental problems are expected when the product is used / handled correctly. In its intended use, the product is not released into the environment.

13. Disposal considerations

www.rxmarine.com

Classification	EU Waste class: 07.01	This material and/or its container must be disposed of as hazardous waste
Disposal considerations		Do not discharge into drains or the environment, dispose to an authorised waste collection point Disposal should be in accordance with local, state or national legislation

14. Transport information

www.rxmarine.com

Proper Shipping Name	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes)	
UN	UN NO.	3082	
	Hazard Class	9	Packing Group
Road/Rail (ADR/RID)			III
	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes)	
	ADR UN No.	3082	
	ADR Hazard Class	9	Termcard
Sear (IMDG)			90GM6-III

Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes)		
IMDG UN No.	3082	IMDG Pack Group	III
IMDG Hazard Class	9	IMDG subrisk	-
IMDG EmS	F-A, S-B		
IMDG Labels	9+MarinePollutant		
IMDG Flashpoint	>62°C		
Air(ICAO/IATA)			
ProperShippingName	Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes)		
ICAO UnNo.	3082	ICAO PackingGroup.	III
ICAO HazardClass.	9	ICAO Labels	9
ICAO subrisk	-		
ICAO Flashpoint	>62°C		
DOT/CFR(USDepartment of Transportation)			
DOTProperShippingName:	Environmentally hazardous substance, liquid, n.o.s. (Alkyl (C3-C8) Benzenes)		
HazardousMaterial	(Alkyl (C3-C8) Benzenes)		
Hazard Class	9	IdentificationNumber	
Product RQ (lbs)	Not Established		
DOTsubrisk:	-		
DOTLabels	9+Marinepollutant		
DOTFlashpoint			

15. Regulatory information

www.rxmarine.com

Risk Phrases

Harmful: may cause lung damage if swallowed (R65) Repeated exposure may cause skin dryness or cracking (R66) organisms, may cause long-term adverse effects in the aquatic environment (R51/53)

Safety Phrases

Do not breathe spray/mists Avoid contact with skin Wear suitable protective clothing, eye/face protection and gloves the environment. Refer to special instructions/Safety data sheets. If swallowed, do not induce vomiting: see a doctor immediately and show this container or label.

16. Other information

www.rxmarine.com

Text of R and S phrase codes used in this safety data sheet:- R51: Toxic to aquatic organisms; R53: May cause long term adverse effects in the aquatic environment; R65: Harmful: may cause lung damage if swallowed; R66: Repeated exposure may cause skin dryness or cracking. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties. The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.