



RX MARINE INTERNATIONAL

Total Solution Total Protection

AN ISO CERTIFIED COMPANY



Fore & AFT RX

Part/Order no:	Packing
RXSOL-16-3012-25	25 Ltr
RXSOL-16-3012-210	210 Ltr

INTRODUCTION:

EMULSION BASED non reactive coating materials which makes thin film barrier on surface after dry. Due to formation of RXSOL THIN barrier film on surface, the cleaning operation after unloading becomes quicker and easier with optimum results.

RXSOL SLIP HOLDBLOCK is a Heavy Duty protective Solution for hold of vessels which carrying corrosive and / or messy cargos such as Sculpture, Salt, Peacock, coal and concentrates. It can be easily removed after discharging of cargo.

FEATURES AND BENEFITS:

- Protects metal against corrosive cargo.
- Safe on all coatings, and to the person- nel handling it.
- Protects paint against cargo penetrati On.
- Environmentally friendly.
- Safe to use in occupied /covered areas.
- Reduces turnaround times.
- Easy to Direct Spray.

Recommendation Dose for smooth surface:

for Sulphur, Salt, etc 100 Liters/Hold for HANDYMAX & 150 Ltrs/Hold for PANAMAX.

&for Peacock, Coal, etc 200 Ltrs/Hold for HANDYMAX & 250 Ltrs/Hold for PANAMAX.

This materials can be use directly with low pressure machine or manually by garden spray pump. in general practice on smooth & clean surface each drums of 210 liters covers 2000 to 2500 sq meter while on rough and rusted surface require more quantities of materials. for HANDYMAX (5 Holds) : In general 500 Ltr to 1000 Ltr RXSOL-22-2210 require to cover area up to 12 meters , i.e. approx 1/2 drum to 1 drum of material is Sufficient for each hold, while.

for PANAMAX (7 Holds): In general 1000 Ltr to 2000 Liters RXSOL-22-2210 require to cover full area. , i.e. approx 3/4 drum to 1.25 drums of material is sufficient for each hold.

This Emulsion is safe to use , But as a precaution goggles & Protective gloves with mask require before use of this materials.

Precaution:

- for Sulphur, Salt, etc 100 Liters/Hold for HANDYMAX & 150 Ltrs/Hold for PANAMAX.
- Newly Painted surface should be fully cured.

Fore & Aft-Rx (Detergents)

For cleaning of hard surfaces,such as decks, tanks, engine-rooms, etc. These two steps are followed:

Step 1: Spray directly on area to be cleaned.

Step 2: With high pressure clean entire emulsified area Due to high emulsification & penetration objects achieves optimal clean- ng results. Due to repulsion activity fore aft-Rx preventing dirt from reforming on the surface.