

## 1. Product and Company Identification

www.rxmarine.com

Product Name RXSOL-10-1730  
Product Type Enviro Brake Parts Cleaner Bulk

### Company Details:

RX MARINE INTERNATIONAL  
105, A wing , BSEL , TECH PARK.  
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333 / 5555 / 9999 / 27611360  
Fax +91 22 2781 1318 ::::AOH :0091 9821214367  
Email [mail@rxmarine.com](mailto:mail@rxmarine.com)

## 2. Composition / Information on ingredients

www.rxmarine.com

COMPONENTS - CHEMICAL NAME AND COMMON NAME (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	Applicable PEL- OSHA	Exposure Limits TLVACGIH	Carcinogen Ref. Source **
HEXANE	110-54-3	Yes	50	50	d
ISOPROPANOL	67-63-0	No	500	400	d

## 3. Hazards Identification

www.rxmarine.com

PRIMARY ROUTES OF ENTRY: [ X ] INHALATION [ ] INGESTION [ ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS

### ACUTE EFFECTS

Inhalation:

Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible unconsciousness or asphyxiation.

Eye Contact:

Slight irritation.

Skin Contact:

Slight irritation due to defatting of skin.

Ingestion:

Possible chemical pneumonitis if aspirated into lungs.

### CHRONIC EFFECTS:

(Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation of hexane may cause nerve damage.

Medical Conditions Generally

May aggravate existing eye, skin, or upper respiratory conditions.

Aggravated by Exposure:

## 4. First Aid Measures

www.rxmarine.com

Eye Contact:

Flush with water for 15 minutes. If irritated, seek medical attention.

Skin Contact:

Wash with soap and water. If irritated, seek medical attention.

Inhalation:

Remove to fresh air. Resuscitate if necessary. Get medical attention.

Ingestion:

DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

## 5. Fire-fighting Measures

www.rxmarine.com

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols)

N/A

N/Auto Ignition Temperature

Auto Ignition Temperature	N/E
---------------------------	-----

Flammability Limits in Air by % in Volume:

% LEL: N/E

% UEL:	N/E
--------	-----

## FLASH POINT AND METHOD

USED (non-aerosols):