

1. Product and Company Identification

www.rxmarine.com

Product Name Molten Salt Calcium Chloride

Product Type RXSOL-68-1436-030

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point ::: Mumbai, Kandla, Kolkata, Chennai, Visakhapatnam, Fujairah, Muscat, Kenya

Phone +91 22 27815540/41

Fax +91 22 2781 1318 :::AOH :0091 9821214367

Email mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	EAC Number
Calcium chloride	10043-52-4
Barium Chloride	10361-37-2
Sodium Chloride	7647-14-5
Proprietary Corrosion Inhibitor	N/A

3. Hazards Identification

www.rxmarine.com

Hazard description: Not applicable.

Information concerning particular hazards for human and environment: Not applicable.

4. First Aid Measures

www.rxmarine.com

General information	No special measures required.
After inhalation	Supply fresh air; consult the doctor in case of complaints.
After skin contact	Generally the product does not irritate the skin.
After eye contact	Rinse opened eye for several minutes under running water.
After swallowing	If symptoms persist consult the doctor.

5. Fire-fighting Measures

www.rxmarine.com

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

Protective equipment: No special measures required.

6. Accidental Release Measures

www.rxmarine.com

Person-related safety precautions: Not required.

Measures for environmental protection: Dilute with plenty of water. Do not allow to enter sewers/ surface or groundwater.

Measures for cleaning/collecting: Absorb with a liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Additional information: No dangerous substances are released.

7. Handling and Storage

www.rxmarine.com

Handling:

Information for safe handling:

Handling:

Information for safe handling: No special requirement

Information about fire - and explosion protection: No special measures required.

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: None.

Information about fire - and explosion protection: No special measures required.

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: None.

8. Exposure controls and personal protection

www.rxmarine.com

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

57-55-6 propane-1,2-diol

WEEL (USA)

10 mg/m³

WEL (Great Britain)

474* 10** mg/m³, 150* ppm

*total vapour and particulates **particulates

Additional information: The lists valid during the making were used as the basis.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection: Not required.

Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests, no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves: The selection of the suitable gloves does not only depend on the material but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material: The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Goggles recommended during refilling.

9. Physical and chemical properties

www.rxmarine.com

General Information

Form

Powder

Colour

White

Odour

Nearly odourless

Change in condition

Melting point/Melting range

Max 150 - 155 °C

Explosion

Product does not present an explosion hazard.

Vapour pressure at 20°C

0.11 hPa

Solubility in / Miscibility with water

Fully miscible.

pH-value (- g/l)

Neutral

Main Ingredients	:	Salt Mixture with Corrosion Inhibitor
Inhibitors	:	6 %
Colour Bright	:	Characteristic Yellowish
Nitrite Content	:	7.5 to 8.5%
Chloride Content	:	0.10% Max.
pH of solution	:	9.5 - 10.5
Working Temp Range	:	155 - 590 Deg.C
Density @ 20 Deg.C	:	1160 Kg/m3
Molten Product Density	:	1.9
Reverse Alkalinity	:	Minimum 15.0 ml
Vapour pressure	:	.07 mbar at 20oC
Heat Transfer Salt TR	:	155
Specific Heat	:	0.39
Skin absorption / Irritation	:	YES
TLV Country	:	
Pollution category 1994	:	III

10. Stability and reactivity

www.rxmarine.com

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Dangerous reactions No dangerous reactions known.

Dangerous decomposition products: No dangerous decomposition products known.

11. Toxicological information

www.rxmarine.com

Acute toxicity:

LD/LC50 values relevant for classification:

Oral	LD50	2000 mg/kg (rat)
Dermal	LD50	20800 mg/kg (rabbit)

Primary irritant effect:

on the skin No irritant effect.

on the eye No irritating effect.

Sensitization No sensitizing effects known.

Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us. The substance is not subject to classification according to the latest version of the EU lists.

12. Ecological information

www.rxmarine.com

General notes: Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13. Disposal considerations

www.rxmarine.com

Product:

Recommendation Smaller quantities can be disposed of with household waste.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

14. Transport information

www.rxmarine.com

Land transport ADR/RID (cross-border)

ADR/RID class: -

Maritime transport IMDG:

IMDG Class: -

Marine pollutant: No

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: -

15. Regulatory information

www.rxmarine.com

Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals.

The substance is not subject to classification according to EU lists and other sources of literature known to us.

16. Other information

www.rxmarine.com

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Main Ingredients	:	Salt Mixture with Corrosion Inhibitor
Inhibitors and	:	6 %

water

6

Inhibitors		
Colour Bright	:	Yellow
Nitrite Content	:	7.5 to 8.5%
Chloride Content	:	0.10% Max.
pH of solution	:	9.5 - 10.5
Odour	:	PRACTICALLY ODOURLESS
Solubility in water	:	SOLUBLE
Melting Point	:	Max 150 - 155 °C
Working Temp Range	:	155 - 540 Deg.C
Density @ 20 Deg.C	:	1160 Kg/m3
Reverse Alkalinity	:	Minimm 15.0 ml

Vapour pressure	:	.07 mbar at 20oC
Hear Transfer Salt TR	:	155
Skin absorption/irritation	:	YES
TLV Country	:	
Pollution category 1994	:	III